ADKII Adirondack II

Mohawk Group

Karastan



DESIGN

 Product Type:
 Woven

 Construction:
 Woven

 Minimum Sq Yd:
 No Minimum

Surface Texture: Textured Patterned Cut & Loop
Pitch: 216 (315 ends per meter)
Woven Pile Weight: 36.0 oz. per sq. yd. (1221 g/m2)

 Finished Pile Thickness:
 .228" (5.79 mm)

 Rows Per Inch:
 10.0 (39.37 per 10 cm)

Dye Method: Yarn Dyed
Fiber Type: Ultron® Nylon

Soil Release Technology: EcoSentry Soil Protection

Density: 5,684
Weight Density: 204,624
Backing Material: Woven

 Width:
 12' width (3.66 m)

 Pattern Repeat:
 1" (W) x 1" (L)



NSF 140: Woven - NSF 140 Gold
Indoor Air Quality: CRI Green Label Plus GLP3802
Declare Label: Declared Red List Free

PERFORMANCE

Flammability: ASTM E 648 Class 1 (Glue Down)
Smoke Density: ASTM E 662 Less than 450
Static Propensity: AATCC-134 Under 3.5 KV

Foot Traffic Recommendation TARR: Heavy

SERVICE

Warranties: Lifetime Limited Woven Wear Warranty, Lifetime Static

w w

646 Spruce



117 Saddle

686 Evergreen

828 858 Lodge Wilderness



727 Cross Country

555 Night Sky



878 Explore

772 Rustic

Karastan



959 Campfire